



Opaque Staining Color

DIRECTIONS

- Apply a thin mark through various methods. Dries to hard tough finish in minutes.

HANDLING

- Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

STORAGE

- Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

- Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

FEATURES

- Performs well on light and dark tinted metals
- Provides excellent coverage properties and opacity
- Thickness can be reduced by adding DYKEM® Remover & Prep
- Fast drying
- Resists cracking, chipping, flaking or scaling
- Will not interfere with moving parts when thinly applied



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid.
Odor	Sweet, Solvent.
Flash Point	24.0 °F (-4.4 °C)
Boiling Point / Range	170 - 257 °F (76.67 - 125 °C)
VOC Content	86.36%, 771 g/L
Evaporation Rate	< 1 (BuAc = 1)
Vapor Density	> 1 (air = 1)
Prop 65 Warning	YES

AVAILABLE IN

Cnt. Type	Net Contents	Units/ Case	Color	Part #
brush-in-cap	8 oz	12	yellow	81405
brush-in-cap	8 oz	12	orange	81413
brush-in-cap	8 oz	12	white	81427
brush-in-cap	8 oz	12	dark blue	81478
brush-in-cap	8 oz	12	red	81491
can	1 gal	4	yellow	81705
can	1 gal	4	dark green	81706
can	1 gal	4	light green	81708
can	1 gal	4	orange	81713
can	1 gal	4	black	81724
can	1 gal	4	light blue	81725
can	1 gal	4	white	81727
can	1 gal	4	pink	81760
can	1 gal	4	purple	81763
can	1 gal	4	dark blue	81778
can	1 gal	4	red	81791



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved